



Summary

The VMAX[®] IP Plus[™] is an easy to use to use PoE NVR that allows you to go from power up to monitoring in less than three minutes! Combine with the DW Witness[™] app to turn the camera on a smartphone or tablet into a surveillance camera that can be viewed and recorded on the NVR. Available with 16 PoE ports, the NVRs can record and manage single-sensor IP cameras up to 4K, with 160Mbps maximum throughput.

Features

- Complete installation, setup and camera configuration in under three minutes!
- CCIP[™] system encryption protects your surveillance system from out of network attacks
- Record and manage single-sensor IP cameras at real-time 30fps up to 4K (3840x2160), with 160Mbps maximum throughput
- Local power for up to 16 IP cameras via resident PoE switch
- myDW[®] Cloud Management Services
- DW Witness[™] turns a smartphone or tablet into an additional surveillance camera
- PathFinder[™] Peer-to-Peer (P2P) remote connection
- Automatic device discovery
- Control any ONVIF[™] camera's setup and features remotely
- 2TB-32TB storage options
- Snapshot Notify[™]: programmable interval camera image verification sent to an email
- Remote management with C3[™] CMS software up to 288 channels
- Event notifications via email, text and C3[™] CMS and push notifications to mobile devices
- Mobile Application for iOS[®] and Android[®] devices and Apple TV[®]
- Dual-stream recording
- Easy drag and drop camera management
- Instant backup during playback
- 4K output for local live and playback display
- Complete analysis with real-time system, network and PoE monitoring
- True HD and VGA simultaneous output support
- 16 sensor inputs, 4 alarm relay outputs
- Advanced H.265, H.264 Linux embedded NVR
- NVR calculation and auto-recording configuration
- Add public view monitors with Spot Monitoring Modules
- Help menu on major functions
- Auto or manual firmware upgrade available
- Screen saver to protect monitor screen
- Import/export configuration between multiple NVRs
- USB mouse and GUI control
- 5 year limited warranty





Accessories (optional)



Dimensions

Unit: Inch (mm)



Specifications

Operating system		Embedded Linux [®]
Video compression		H.265, H.264
System	Channel	16 channel
	Number of PoE	16 Ch
	Maximum resolution	IP camera maximum 4K (3840x2160)
	Communication protocol	ONVIF [®]
Display	PoE type	1Gbps, 802.3at
	Speed	480fps
Video output	Screen mode	1, 4, 9 and 16
	Monitor	True HD and VGA
Recording speed	Resolution	1024x768, 1280x720, 1280x1024, 1920x1080, 2560x1600, 3840x2160 (4K)
	Maximum throughput	Up to 360fps up to 4K resolution
Maximum HDD bay		4x HDDs, up to 32TB storage
Recording resolution		Dual-stream
Recording modes		Continuous, scheduled, sensor and motion detection, pre- and post-alarm, emergency, quick backup
Playback and search	Speed	x1, x2, x4, x8, x16, x32, x64, x99
	Function	Timeline, calendar (date and time), event search, thumbnail search, smart motion search
Audio input/output		1 output
Alarm input/relay output		16 inputs/4 outputs
PTZ control		RS-485, ONVIF
Transaction verification		Text-in Based (USB to Serial support, TCP/IP Network)
LAN		Gigabit Ethernet (RJ45)
Access	Web viewer	Live, playback and configuration up to 10 multiple connections
	Client monitoring software	Mac [®] , C3 CMS, DW Mobile Plus mobile app
Backup device		Local backup by USB, network backup by CMS
System recovery after power failure		Auto-reboot and journaling file system
Other functions	Firmware upgrade	FTP, USB and CMS over Network
	Back-up	Import and export settings, watermark and AVI file backup
	Special features	Local PoE switch Snapshot Notify: Programmable interval camera image verification sent to an email Event notifications via email, text and C3 [™] CMS and push notifications to mobile devices Real-time temp alert Digital zoom in live and playback
	Mobile client	DW Mobile Plus app, DW Witness
Health check		Real-time system, network and PoE status monitoring
System operation		IR remote controller (sold separately), USB mouse, PTZ control by keyboard (optional)
Power requirements		110-240V A/C
Power consumption		300 W total power budget, 5.5A, 9.37W per PoE channel (simultaneous)
Total PoE power budget		150W
Maximum power per port		30W
Operating temperature and humidity		41-104 °F (5-40 °C) / 20-90% RH
Dimension (W x D x H)		17.32" x 15.66" x 2.79" (440 x 397.8 x 70 mm), 1.5U
Certification		CE, FCC, KCC, WEEE, RoHS
Warranty		5 year limited



Increase sales and profitability. Sign up and become a DW Channel Partner today!



☎ : 866.446.3595 ✉ : sales@digital-watchdog.com 🌐 : www.digital-watchdog.com




Available Models

- DW-VP16P- no local storage.
- DW-VP163T16P - 3TB local storage.
- DW-VP164T16P - 4TB local storage.
- DW-VP166T16P - 6TB local storage.
- DW-VP169T16P - 9TB local storage.
- DW-VP1612T16P - 12TB local storage.
- DW-VP1616T16P - 16TB local storage.
- DW-VP1618T16P - 18TB local storage.
- DW-VP1624T16P - 24TB local storage.
- DW-VP1632T16P - 32TB local storage.



Increase sales and profitability. Sign up and become a DW Channel Partner today!



 : 866.446.3595



: sales@digital-watchdog.com



: www.digital-watchdog.com

